MAXIBLUE®





PERFORMANCE

1) 21 dba

MAX FLOW	MAX HEAD	MAX LIFT
14 L/ HOUR	8 METRES	8 METRES

Designed for high humidity environments and with high performance, the MAXIBLUE® is ideally suited for mid range air conditioning systems. Its exceptional reliability is backed by a multi year warranty and with class leading performance/suction lift, the MAXIBLUE® is ideal for installations in environments that are both demanding and expensive to access for maintenance.

SENSING OPTION

MAXIBLUE® pump available with:

RESERVOIR	drainstik® sensor	TEMPERATURE SENSOR
X87-701	X87-702	X85-703



NO COMPLEX SFT UP

BLUEDIAMOND® technology can deal with the variable outputs of condensate without the need for additional sensors or overly complex performance settings.




NO WIRELESS CONNECTIONS

Plug in and wireless connections to review pump history or run times before premature failures are not needed due proven inherently reliable technology.


UNIT 8-14 KW

PERFORMANCE



DIMENSIONS (MM)





DISCHARGE PIPE RUN




V (VERTICAL)	H (HORIZONTAL)
8 M	0 M
7 M	3 M
6 M	6 M
5 M	9 M
4 M	12 M
3 M	15 M
2 M	18 M
1 M	21 M
TI MANUBULES	

The MAXIBLUE® can be mounted in any orientation up to 8m away from the A.C unit.

WHY UPGRADE TO ROTARY DIAPHRAGM TECHNOLOGY

PERISTALTIC PUMPS

- Have the ability to run dry, pumping a mixture of air and water.
- Can be mounted remotely, offering easier and more installation possibilities.



- Tubing will need to be replaced with frequent intervals due to wear.
- High noise levels due to pulsating flow instead of smooth.
- Struggle to get a high performance from a large sized pump.

ROTARY DIAPHRAGM TECHNOLOGY OFFERS ALL THESE SOLUTIONS PLUS:

No tubing to replace at frequent intervals, Rotary Diaphragm technology is service and maintenance free.

Synchronous motor technology offers more compact pump without sound complaints from gearbox motor.



Low cost alternative to peristaltic pumps in the long term.

