

DATA SHEET

## PE 5000

### Peristaltic pump

Sauermann® part #: PE5000SIUN23

#### Compact pump

The peristaltic pump is controlled by a signal from the air conditioning compressor. It stops 3 minutes after the compressor stop.

This pump must not be used:

- With an "Inverter" air conditioning unit
- In continuous run.

### Benefits



#### High performance

- High discharge head up to 12 m.
- Low noise level.



#### Easy and quick maintenance

- Its replaceable head and easy access tube reduce maintenance costs.



#### Easy to install


- Compact form.
- IP65 protection allows installation without ventilation.

### Kit content

- Peristaltic pump PE5000
- Cable: 1.7 m, including 2 wires for power supply (P & N), 1 wire for compressor signal
- Easy «1 screw» sliding plastic bracket
- Ø 15 mm to Ø 6 mm adaptor + pale yellow rubber (Ø 15 x 35 mm) - (PE5003)

## Technical specifications

Max. flow rate	6 l/h
Max suction head	2 m
Max discharge head	12 m
Sound level in application at 1m: ≤ 30 dBA (Measured in Sauermann acoustic lab, pump operating with water)	
Mains supply	230 V~ 50 Hz - 11 W
Insulation class	□ (double insulation)
Detection type	Compressor's live (Cooling signal)
Protection	IP65
Pump dimensions	L 109 x W 110 x H 91 mm
Safety standards	CE & EAC
RoHS directive	Compliant
WEEE directive	Compliant
Packaging	1,0 kg
Masterpack	16 pieces






## Applications

For use with any air-conditioning units up to 8 kw:

- Wall mounted
- Ceiling suspended
- Computer room air conditioning
- Ducted

## Accessories

Name	#Part
 <b>Clear PVC hose</b> Ø int. 6 mm (1/4")	ACC00909 (5 m) ACC00910 (50 m) ACC00914 (Braided, 50 m)
 <b>Float detector</b> used to operate an additional alarm or to witch on the pump	ACC00601
 <b>Replacement head</b> For PE5000; PE5100 and PE5200	PE5001
 <b>6 self-sealing fittings for hose</b> Ø int. 6 mm (1/4")	ACC00919
 <b>Replacement hose</b> For PE5000, PE5100 and PE5200	PE5002

## Actual flow rate (l/h)

Total tube length (Ø int. 6 mm; 1/4")		
Max suction head	Max discharge head	The discharge flow is constant whatever the discharge or the suction head
2 m	12 m	6